



» **PRODUCT BULLETIN**

Cesa™ Clean Additives

Cesa™ Clean masterbatch additives are formulated to effectively clean process tooling and machinery during material or color changeovers. They are a cost-effective way to help maintain critical production uptime and increase manufacturing efficiencies.

WHEN TO USE CESA CLEAN

As a best practice, Cesa Clean adds value when used for:

- Color changeovers
- Material and formulation changes
- Shutdown or startup
- Machine maintenance

WHY USE CESA CLEAN

Some of the ways you can benefit from consistently using Cesa Clean:

- Improve production uptime with faster color changeovers
- Reduce wasted melt puddle material
- Reduce resin use during purging
- Non-abrasive and safe to use on precision equipment

Cesa Clean solutions are available for use in a variety of processing conditions and operating temperatures. They are effective for cleaning both extrusion and injection molding equipment and have the added benefit of being recyclable.

PRODUCT NO.	DESCRIPTION	CHARACTERISTICS	PROCESSES
CC10120195WE	Multi-purpose purge concentrate that is miscible with all resin systems	Performance up to 280°C	Extrusion, molding, injection and film processes

Specialized purge concentrates may be available for engineering resins or for specific performance needs. Contact your Avient representative for more information.

1.844.4AVIENT
www.avient.com



Copyright © 2023, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.