

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****1169-B LACQUER HARDENER**Version Number 1.7  
Revision Date 03/13/2014Page 1 of 10  
Print Date 3/14/2014**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**  
8155 Cobb Center Drive, Kennesaw, GA 30152Telephone : 1 (440) 930-1000 or 1 (866) POLYONE  
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure  
number or accident).**Product name : 1169-B LACQUER HARDENER  
Product code : FO00008142  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS-No.	Weight percent
1-Methoxy-2-propanol	107-98-2	1 - 5
1-Butanol	71-36-3	5 - 10
Xylenes (o-, m-, p- isomers)	1330-20-7	10 - 30
Toluene	108-88-3	10 - 30
Methyl isobutyl ketone	108-10-1	10 - 30

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

Flammable. May be harmful if inhaled. Harmful if swallowed. May cause skin irritation. Flammable liquid and vapor. Vapors may be irritating to eyes and respiratory tract. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

**POTENTIAL HEALTH EFFECTS****Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**Inhalation : Excessive inhalation of product vapors may cause respiratory irritation, headaches, dizziness, and/or nausea.  
Ingestion : May be harmful if swallowed. May cause nausea, abdominal spasms and irritation of the mucous membranes.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7  
Revision Date 03/13/2014

Page 2 of 10  
Print Date 3/14/2014

Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin : Prolonged or repeated skin contact can cause de-fatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions Aggravated by Exposure:** : Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.

**4. FIRST AID MEASURES**

Inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Seek medical attention after significant exposure.

Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. Seek medical attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIREFIGHTING MEASURES**

Flash point : Less than 75 °F (24 °C)

**Flammable Limits**

Upper explosion limit : no data available

Lower explosion limit : no data available

Auto-ignition temperature : no data available

Suitable extinguishing media : Carbon dioxide blanket, Water, Foam, Dry chemical.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7  
Revision Date 03/13/2014

Page 3 of 10  
Print Date 3/14/2014

the soil. Should not be released into the environment.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**7. HANDLING AND STORAGE**

Handling : Flammable liquid. Keep away from flames, hot surfaces, and sources of ignition. Use of non-sparking or explosion-proof equipment may be necessary. Never use compressed air for transferring product. Ensure all equipment is electrically grounded before beginning transfer operations. Take measures to prevent the build up of static electricity. Use only in area provided with appropriate exhaust ventilation.

Storage : Store below 120 °F (49 °C) Keep containers tightly closed in a cool, well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammable Liquid. Check local fire regulations for sprinkler or explosion proof storage location requirements.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory protection : Airborne contaminant levels should be maintained below the occupational exposure guidelines. When respiratory protection is required, use an approved air-purifying or positive pressure supplied-air respirator, depending upon potential airborne contaminant concentrations. Employees using respirators must be properly trained.

Eye/Face Protection : Wear goggles or face shield during operations that present a splash potential.

Hand protection : Protective gloves Protective gloves. Refer to equipment supplier to ensure protection.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Ensure adequate ventilation, especially in confined areas.

Engineering measures : Provide general and/or local exhaust ventilation to control airborne contaminant levels below the exposure guidelines.



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7  
Revision Date 03/13/2014

Page 4 of 10  
Print Date 3/14/2014

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7

Revision Date 03/13/2014

Page 5 of 10

Print Date 3/14/2014

Components	Value	Exposure time	Exposure type	List:
Xylenes (o-, m-, p-isomers)	100 ppm	Time Weighted Average (TWA):		ACGIH
	150 ppm	Short Term Exposure Limit (STEL):		ACGIH
	100 ppm 435 mg/m3	PEL:		OSHA Z1
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		MX OEL
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Toluene	20 ppm	Time Weighted Average (TWA):		ACGIH
	100 ppm 375 mg/m3	Recommended exposure limit (REL):		NIOSH
	150 ppm 560 mg/m3	Short Term Exposure Limit (STEL):		NIOSH
	200 ppm	Time Weighted Average (TWA):		OSHA Z2
	300 ppm	Ceiling Limit Value:		OSHA Z2
	500 ppm	Maximum concentration:		OSHA Z2
	100 ppm 375 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	150 ppm 560 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	50 ppm 188 mg/m3	Time Weighted Average (TWA):		MX OEL
	1-Butanol	20 ppm	Time Weighted Average (TWA):	
50 ppm 150 mg/m3		Ceiling Limit Value and Time Period (if specified):		NIOSH
100 ppm 300 mg/m3		PEL:		OSHA Z1
50 ppm 150 mg/m3		Ceiling Limit Value:		OSHA Z1A
50 ppm 150 mg/m3		Ceiling Limit Value:		MX OEL
Methyl isobutyl ketone		20 ppm	Time Weighted Average (TWA):	
	75 ppm	Short Term Exposure Limit (STEL):		ACGIH
	50 ppm 205 mg/m3	Recommended exposure limit (REL):		NIOSH
	75 ppm 300 mg/m3	Short Term Exposure Limit (STEL):		NIOSH

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7  
Revision Date 03/13/2014

Page 6 of 10  
Print Date 3/14/2014

	100 ppm 410 mg/m3	PEL:		OSHA Z1
	50 ppm 205 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	75 ppm 300 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	50 ppm 205 mg/m3	Time Weighted Average (TWA):		MX OEL
	75 ppm 307 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
1-Methoxy-2-propanol	100 ppm	Time Weighted Average (TWA):	Vapor.	ACGIH
	150 ppm	Short Term Exposure Limit (STEL):	Vapor.	ACGIH
	50 ppm	Time Weighted Average (TWA):		ACGIH NIC
	100 ppm	Short Term Exposure Limit (STEL):		ACGIH NIC

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: liquid	Evaporation rate	: Faster than Butyl Acetate
Appearance	: liquid	Specific Gravity	: Not determined
Colour	: NO PIGMENT	Bulk density	: Not applicable
Odour	: solvent-like	Vapour pressure	: not determined
Melting point/range	: Not applicable	Vapour density	: Heavier than air.
Boiling Point:	: no data available	pH	: not determined
Water solubility	: negligible		

**10. STABILITY AND REACTIVITY**

Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. Heat, flames and sparks.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), other hazardous materials, and smoke are all possible.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7  
Revision Date 03/13/2014

Page 7 of 10  
Print Date 3/14/2014

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
107-98-2	1-Methoxy-2-propanol	Systemic effects	Eyes, Skin, Respiratory system, central nervous system (CNS).
		Irritant	Eyes, Skin, Respiratory system.
71-36-3	1-Butanol	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, central nervous system (CNS).
1330-20-7	Xylenes (o-, m-, p-isomers)	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system, Liver, Kidney, central nervous system (CNS), digestive system.
108-88-3	Toluene	Systemic effects	central nervous system (CNS), Liver, Kidney, urinary system.
		Irritant	Skin, Eyes.
108-10-1	Methyl isobutyl ketone	Systemic effects	central nervous system (CNS), reproductive system.
		Irritant	Eyes.

**LC50 / LD50**

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
107-98-2	1-Methoxy-2-propanol	LC50 LC50 Oral LD50Oral LD50 Dermal LD50 Dermal LD50	10000 ppm  11,700 mg/kg 7.51 g/kg 13 gm/kg 13 g/kg	rat rat mouserat rabbit rabbit
71-36-3	1-Butanol	LC50 Oral LD50 Dermal LD50	8000 ppm/4H 790 mg/kg 3,400 mg/kg	rat rat rabbit
1330-20-7	Xylenes (o-, m-, p-isomers)	LC50 LC50 Oral LD50Oral LD50 Dermal LD50 Dermal LD50	5000 ppm/4H  4,300 mg/kg 4,300 mg/kg > 1,700 mg/kg 43 g/kg	rat rat ratrat rabbit rabbit
108-88-3	Toluene	LC50 Oral LD50 Dermal LD50	49 gm/m3 636 mg/kg 14100 ul/kg	rat rat rabbit

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**1169-B LACQUER HARDENER**

Version Number 1.7

Revision Date 03/13/2014

Page 8 of 10

Print Date 3/14/2014

108-10-1	Methyl isobutyl ketone	LC50 LC50 Oral LD50 Dermal LD50	100 gm/m3  2,080 mg/kg 16,000 mg/kg	rat rat rat rabbit
----------	------------------------	--	--	-----------------------------

**Carcinogenicity**

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
108-10-1	Methyl isobutyl ketone	no	2B	no

**IARC Carcinogen Classifications:**

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

**NTP Carcinogen Classifications:**

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : no data available
- Environmental Toxicity : no data available
- Bioaccumulation Potential : no data available
- Additional advice : no data available

**13. DISPOSAL CONSIDERATIONS**

- Product : Dispose of properly. Do not dump into sewers, on the ground, or into any body of water. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

- U.S. DOT Classification
- Proper Shipping Name: Paint related material
- Technical Name:



**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****1169-B LACQUER HARDENER**Version Number 1.7  
Revision Date 03/13/2014Page 9 of 10  
Print Date 3/14/2014

Hazard Class / Division 3  
UN Number UN1263  
Packing Group II  
Label Required 3

ICAO/IATA Refer to specific regulation.  
IMO/IMDG (maritime) Refer to specific regulation.

**15. REGULATORY INFORMATION**

## US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

## US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product
Xylenes (o-, m-, p-isomers)	1330-20-7	100 lbs	334 LB

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

## SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

## SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
XYLENE (MIXED ISOMERS)	1330-20-7	10.00 - 30.00
TOLUENE	108-88-3	10.00 - 30.00
N-BUTYL ALCOHOL	71-36-3	5.00 - 10.00
METHYL ISOBUTYL KETONE	108-10-1	10.00 - 30.00

## Canadian Regulations:

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****1169-B LACQUER HARDENER**Version Number 1.7  
Revision Date 03/13/2014Page 10 of 10  
Print Date 3/14/2014

## National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Xylenes (o-, m-, p- isomers)	1330-20-7	10.00 - 30.00	
Toluene	108-88-3	10.00 - 30.00	
1-Butanol	71-36-3	5.00 - 10.00	
Methyl isobutyl ketone	108-10-1	10.00 - 30.00	

WHMIS Classification : D2A, B2

## WHMIS Ingredient Disclosure List

CAS-No.
108-88-3
71-36-3
108-10-1
107-98-2

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

## National Inventories:

Australia AICS : Not determined  
China IECS : Not determined  
Europe EINECS : Listed  
Japan ENCS : Not determined  
Korea KECI : Not determined  
Philippines PICCS : Not determined**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.